



RECOMMENDED PCB LAYOUT(TOP VIEW)

备注:

- 1.材质:
 - 1.1胶芯: LCP+30%G.F UL94V-0
 - 1.2端子: 磷铜, T=0.12mm; 镍底, 镀金Xμ”
 - 1.3外壳: 不锈钢, T=0.30mm; 表面镀镍100μ”或亮锡100μ”
- 1.4接地片: 不锈钢, T=0.10mm;
- 1.5卡片: 不锈钢, T=0.15mm;
- 2.主要特性:
 - 2.1额定电流: 0.5A
 - 2.2接触阻抗: 30mΩ MAX
 - 2.3绝缘阻抗: 100MΩ MIN 250V DC
 - 2.4耐压测试: 250V AC
 - 2.5沾锡性: 温度250? °C, 时间5?.5s
 - 2.6整体插入力: 3.57kgf MAX
整体拔出力:1.02kgf MIN
 - 2.7使用寿命: 10000次
 - 2.8工作温度: -30°C~+80°C

TOLERANCES		东莞市欧盈电子科技有限公司				
.X	±0.30	DONGGUAN OYELEC TECHNOLOGY CO.,LTD				
.XX	±0.20	TEL:0769-82313999 FAX:0769-82001959				
.XXX	±0.15	TITLE:0				
ANGLES	±3.00°	USB Type-C/F 母座11.95前插后贴				
APPD.:		PART NO.:				
CHECK:		OY-S001-TYAF004-1-012				
DRAWN:		DRAWING NO.:				
REV.:	SIZE:	UNIT:	SCALE:	SHEET:		
A/0	A4	M M	1 : 1	1 / 1		